

QHD Offset Range

With a working width of 1.2, 1.6 or 2.0 metres this fully offset, heavy duty flail mower has been specifically designed for professionals that require a high output verge mower for intensive use.

A hydraulic verge floatation system and belt driven spiralled rotor fitted with heavy duty flails ensure a quality finish even in the most demanding environments. Safety features include a mechanical safety breakaway and a cushioned drive system that protects vital components from any sudden load impacts.

A front mounting build option is also available for users looking to compliment an existing verge mowing configuration for greater productivity.

- 1.2, 1.6 and 2.0 metre Cutting Widths
- Left Hand and Right Hand Build Options
- Front or Rear Mounting Options
- Heavy Duty High Power Gearbox
- Hydraulic Sideshift
- 600mm Hydraulic Offset
- 540RPM or 1000RPM PTO
- Over-run PTO Protection
- Double Skin Body
- Twisted Flail
- Large Diameter Rear Roller
- 15mm to 150mm Cutting Heights
- 50mm Maximum Cutting Diameter

MODEL	1.20M	1.60M	2.0M
Cutting Width	1.20m	1.60m	2.00m
Machine weight	TBC	822kg	900kg
3-point linkage-mounting	Std	Std	Std
Cutting Range	15-150mm		
Hydraulic Offset	600mm	600mm	600mm
PTO Speed	540/1000	540/1000	540/1000
Over-run PTO protection	Std	Std	Std
Rotor Speed	2000 rpm	2000 rpm	2000 rpm
Number of flails	38	48	66
Max. upward movement	+90°	+90°	+90°
Max. downward movement	-60°	-60°	-60°
Tractor power required	50hp	60hp	70hp

